

PARADOR

Technical leaflet:

Naturally oiled floors

Ingredients

Parador natural oil is a "high solid product" based on natural plants: sunflower-, soy- and safflower oils.

Properties

Open-pored surface treatment based on natural plant raw materials. During the factory treatment the oil penetrates the wood and the wood surface retains its natural, resistant texture. After hardening, the surface is open and breathable. The wood therefore provides a balanced moisture content and a healthy indoor climate. Humidifiers are necessary, however, if the indoor climate tends to be too dry. (approx. 35-60 % rel. humidity = pleasant indoor climate)

Resistance

The naturally oiled surface is tested in accordance with EN 13442 (determining the chemical resistance of wood floors) and classified in Group 4 (minimal changes). The hardened surface is tested in accordance with DIN 53160 Part 1 and 2 (resistant to saliva and perspiration) and is suitable for children's toys in accordance with EN 71 Part 3 (migration of certain elements). You can find further information about the usage properties of the Parador floor on the technical datasheet for the product in question.

Environmental information

Parador natural oil does not contain any preservatives or any biocidal active ingredients and is not subject to labelling according to the Ordinance on Hazardous Substances.

General information

Clean the floor after laying and at future intervals with a vacuum cleaner (attached brushes) and/or broom). Please find instructions about how to wipe the floor regularly on the information provided by the respective manufacturer of the care product. Steam cleaners, scouring powder, scouring milk or other abrasive cleaning products must not be used. Use entrance mats and fit soft felt pads to furniture and chairs. Only use office chairs with soft castors and lay standard protective mats in the castor area.

Initial care treatment / Maintenance / Repair

To retain the floor's value over the long term and depending on its demands/strain, an initial care treatment is recommended and regular maintenance is necessary.

"In heavier/strong stressed areas and/or products: colorized, with modified structure surfaces (Trendtime 8) as well as rustic finishes, we recommend to maintain the floor with "Saicos Ecoline Profipflegeöl" after the installation. This is a professional oil for maintenance and care and it should be applied by a professional parquet floor installer (see Parador price list)."

In addition to the recommended products of the company Saicos, which can be found in the price list, various oil-, oil/wax- or wax-systems are available on the market. You should decide for a system.

The Parador naturally oiled surface can be treated with all standard cleaning and care products for air-drying or oxidative-drying naturally oiled surfaces.

! Please take note of your chosen supplier's respective instructions and labelling !

Below are more suppliers of cleaning and care products:

- Saicos www.saicos.de
- WOCA www.wocashop.de
- Eukula www.eukula.de (Dr. Schutz)
- OSMO www.osmo.de
- LOBA www.loba.de
- Naturhaus www.naturhaus.net
- PNZ www.pnz.de

Changed by:	QMB	File name:	20161016_PA_TDS_Naturoel_EN
Date:	2010.12.10	Update:	www.parador.de
Our technical datasheets are constantly updated and adapted to the latest technology. This version replaces all earlier editions and is valid from:			09.08.2016