


























Product quality		Basic 30 Vinyl with HDF core board		Basic 4.3 Solid vinyl	
<b>Formats</b>		1207 x 216 x 9,4 mm	2200 x 216 x 9,4 mm	1209 x 219 x 4,3 mm	598 x 294 x 4,3 mm
<b>Packaging</b>	<b>Pack:</b>	7 Elements / 1,825 m <sup>2</sup> / 17 kg	5 Elements / 2,376 m <sup>2</sup> / 22,9 kg	9 Elements / 2,383 m <sup>2</sup> / 20,2 kg	11 Elements / 1,934 m <sup>2</sup> / 15 kg
	<b>Pallet:</b>	36 Pack / 65,70 m <sup>2</sup> / 627 kg	33 Pack / 78,410 m <sup>2</sup> / 783,7 kg	42 Pack / 100,08 m <sup>2</sup> / 863,4 kg	48 Pack / 92,83 m <sup>2</sup> / 735 kg
<b>Tolerances DIN EN 14085 (Vinyl with HDF-core board)</b>			<b>Tolerances DIN EN ISO 10582 (Solid vinyl)</b>		
<b>Squareness of the elements (≤ 0.50mm)</b>			≤ 0.30 mm		
<b>Determination of Linearity (≤ 0.30 mm)</b>			≤ 0.15 mm/m		
<b>Flatness concave / convex</b>	<b>lengthwise (≤ 0.50/≤ 1.0 %)</b>		≤ 0.35/≤ 1.0 %		
	<b>wide (≤ 0.10/≤ 0.15 %)</b>		≤ 0.10/≤ 0.10 %		
<b>Surface flushness</b>	<b>(average ≤ 0.15 mm)</b>		average ≤ 0.10 mm		
	<b>(max. ≤ 0.20 mm)</b>		max. ≤ 0.15 mm		
<b>Opening between installed elements</b>	<b>(average ≤ 0.15 mm)</b>		average ≤ 0.05 mm		
	<b>(max. ≤ 0.20 mm)</b>		max. ≤ 0.10 mm		
<b>Guarantee</b>	Domestic area	10 Years (According Parador guarantee conditions)		<b>Notes</b>	<ul style="list-style-type: none"> <li>- Released for glue-down only by PARADOR application technology department</li> <li>- cleaning an maintenance see instructions</li> <li>- technical changes reserved</li> </ul>
	Commercial area	-			
 <b>EN 14041:08</b>		 Qualität Fertigung überwacht Funktionalität <a href="http://www.tuv.com">www.tuv.com</a> ID 0000039917		 	

Classification		
	Test method	Rating
 <b>Utility class 23</b> domestic areas with intensive use	EN 14085 DIN EN ISO 10582	Living room, hall, kitchen, home office
 <b>Utility class 31</b> commercial areas with low use	EN 14085 DIN EN ISO 10582	Classrooms, small offices, shops
 Wear layer	EN 429	0,3 mm
 Wear behaviour	DIN EN ISO 10582	T
 Surface Coating		PUR
 Reaction to fire	EN 13501-1	Vinyl with HDF core board: B <sub>fl</sub> s1 Solid vinyl: C <sub>fl</sub> s1
 Slip resistance	EN 13893 EN 14041	μ ≥ 0,35 DS
 Staining resistance	EN 423	Grade 0, no visible changes
 Light fastness	EN ISO 105 – B02	Blue wool scale: Stage ≥ 6
 Resistance to roller castor chairs	EN 425	Type W, no visible changes
 <b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	Vinyl with HDF core board: 0,068 m <sup>2</sup> *K/W Solid vinyl: 0,025 m <sup>2</sup> *K/W
 Moving a furniture leg	EN 424	No visible changes
 Indentation-residual	EN 433	≤ 0,10 mm
 Formaldehyde (E1 = 0.1 ppm)		≤ 0,05 ppm (only vinyl with HDF core board)
 Acoustical - Impact noise reduction	ISO 717-2	Vinyl with HDF core board: 15 dB Solid vinyl: 13 dB (on Akustik-Protect)
 Dimensional stability	EN ISO 23999	Vinyl with HDF core board: lengthwise and crosswise ≤ 0,1 % Solid vinyl: ≤ 0,25 %
 Thickness swelling	ISO 24336 (≤ 18 %)	≤ 16 % (only vinyl with HDF core board)
 Antimicrobial activity	ISO 22196	Antibacterial
 Slip resistance on an inclined plane	DIN 51130	Brushed / stone texture: R 9 Rough sawn / wood texture : R 10
 REACH		Current requirements are complied
 Disposal		Private waste disposal with normal household waste / bulky waste possible

Changed:	QMB Parador	File:	20161016_PA_TDS_Basic_EN
Date:	01.06.2012	Updates at:	<a href="http://www.parador.de">www.parador.de</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			16.10.2016